PHOTO SENSORS LASER TYPE


LT20R/LD-S33R series

- A Red Semiconductor laser (class 2) is used!
- A fine object of (4mm is detectable over the long distance of 20m.
- Compact design by high density mounting. (LD-S33R)
- A fine mark can be detected from a great distance.

Implement safety measures according to the instruction manual.



OUTPUT CIRCUIT



LT20R/LD-S33R series


SPECIFICATIONS

Model	LD-S33R	LT20RB
Detection	Diffuse Reflecton	Through beam
Range	300mm ± 100mm	20m
Power supply	12 - 24VDC ± 10% Ripple 10% Max.	
Current Consumption	38mA(Max.)	100mA(Max.)
Output mode	Open collector NPN / PNP 2 output	Open collector NPN output
	Rating: 100mA, DC30V Max.	Rating : Sink current (100mA, DC30V Max.)
Operating mode	Light-on / Dark-on selectable	
Response time	0.5msec(Max.)	
Spot diameter	2mm(at range 300mm)	
Minimum object's	0.5mm(Black mark on the white paper at range 300mm)	
mark width	0.3hilit Black mark on the write paper at range 300hilit)	
Light source	Red Laser Diode(650nm) Class 2	Red semiconductor laser wave length(670mm)
(wave length)		
Indicator	Operation:Red, Stability : Green	
Sensitivity volume	8 turn non-stopper potentiometer	
Short circuit protection	Built-in	
Material	Body:Zinc dicast & Alminum	Case : Polyfcarbonate
	Head : ABS	Lens : Acrylic
	Indicator panel : Polycarbonate	Head : PBT
	Lens : Glass	
Connection	Flying lead 2m(outer dia 4.5mm)	Flying lead 3m(outer dia 4.2mm)
	0.25sq × 5 cores	Trns : 0.3 sq × 2 cores , Rcvr : 0.3 5q × 3 cores
Weight	300g(Max.)	Trns: 150g, Rcvr: 100g (Max.)


ENVIRONMENT


Ambient Light	Sunlight : 10,000lx(Max.)	
Ambient Light	Incandescent: 3,000lx(Max.)	
Operating temp.	- 10 ~ + 40	
Humidity	35 ~ 85 % RH	
Protection	LD-S33R : IP66 , LT20RB : IP64	
Vibration	10Hz to 55Hz, 1.5mm Amplitude, 2 hours 3 directions	
Shock resistance	AC1,000V 1min	
Insulation resistance	20M Min(DC500VM)	

PANEL DESCRIPTION (LD-S33R)



ACTIVE BEAM WIDTH





CAUTION for Laser Products

(Class 2: The semiconductor lasers used in these products are applicable to the following classes of JISC6802 "Radiation Safety Standard of a Laser product".

- · Class 1: (Intrinsically safe by their technological designs)
- Class 2: (Visible light and of sufficiently low output so that physical damage can be avoided by the human protection reaction)

Because laser light is non-divergent, never expose your eyes to laser light. Never look into the laser radiation port of the sensor when it is connected to the power box. Direct exposure to laser light may cause damage to your eyes. Be careful to never let the laser light shine into your eyes.

This laser product has the following warning and instruction labels on the unit in order to inform users of the dangers. Do not remove the labels. After installing the sensor, attach the labels onto places that are easily visible.

The laser radiates in an oval form due to a feature of the semi-conductor laser. Also, it shows the following diffraction pattern due to the light diffraction phenomena.

This product is highly subject to deterioration or destruction by current surge or static electricity as it uses a semiconductor laser.

The laser diode has a circuit to maintain brightness built in, and therefore as the output reduces, the current increase to maintain the brightness at a certain level. Therefore, give sufficient allowance to the power supply.

Do not turn the power ON/OFF rapidly.

DIMENSIONS

